

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

CARPET & SHEET VINYL **ADHESIVE REMOVER**

FORMULA

626

BIODEGRADABLE
ODORLESS
NON-FLAMMABLE
WATER-BASED

PRODUCT DESCRIPTION:

SENTINEL 626 CARPET & SHEET VINYL ADHESIVE REMOVER is a powerful, biodegradable, formulation designed specifically for quickly removing latex, acrylic, and pressure-sensitive adhesives from concrete, terrazzo, ceramic, and vinyl tile or wood substrates.

DIRECTIONS: *(Always follow product label instructions for best results.)*

REMOVAL OF LATEX, ACRYLIC, & PRESSURE-SENSITIVE ADHESIVES

Step 1. Apply 626 directly onto adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the surface wet. Allow 626 to soak and penetrate for 30-60 minutes.

Step 2. Scrape softened adhesive from the floor (razor scrapers or squeegees are preferred). Repeat **Steps 1 and 2** if necessary. Dispose of all waste.

Step 3. Rinse the sub-floor thoroughly with clean water. Allow surface to completely dry.

REMOVAL OF SHEET VINYL/LINOLEUM BACKING: Once the wear layer is removed, mix 1 part HOT water to 4 parts 626 (1 quart of HOT water to 1 gallon of 626) and apply directly to the remaining backing. Maintain even coverage and a wet surface for 1-2 hours or until backing/adhesive can be easily removed together with a floor scraper. Rinse the surface with clean water and allow to dry.

REMOVAL OF CARPETING: Using a utility knife, cut the carpeting into 12" strips, making sure to cut through the carpeting to the sub-floor). Mix 2 parts HOT water to 1 part 626 (2 gallons HOT water to 1 gallon 626) and pour directly onto carpet. Maintain even coverage and completely saturate carpeting. Allow to soak for 4 hours, or overnight. Remove carpet strips and follow latex removal procedures for removing remaining adhesive.



For additional information or assistance with this product, please call Sentinel Customer Service at, **800-373-0633**.

SPECIFICATIONS:

APPEARANCE	CLEAR
APPROXIMATE BOILING POINT	212°F
ODOR	NONE
SPECIFIC GRAVITY (60°F)	>1
FLASHPOINT	NONE
%VOC	not greater than 35g/L*

See reverse side for
Material Safety Data Sheet (MSDS)

*When determining VOC concentrations in accordance with the requirements set forth by the California Air Resource Board (CARB) and the Ozone Transport Commission (OTC), effective 01-01-2009.