

PRE-SPRAY

RTU pH 11.3 - 11.9

1-2 oz. : gal

Heavily Soiled & Restaurant Carpets

# Soil Break™

High Powered Powder Enzyme Carpet Pre-Spray

**Soil Break** an ultra-concentrated powder that is ideal for pre-spraying of restaurant carpets, automotive repair centers, and other carpets that are subjected to massive amounts of oil and grease based soiling. **Soil Break** is a synergistic concentration of enzymes, solvents, surfactants and builders that work together to tackle the most stubborn build-up of caked on oil, grease, protein and sticky soils in the most challenging environments.




If for any reason you are not thrilled with the performance of **Soil Break** return it to your distributor and we'll get you a product that does.

Net Contents:  
6.5 Pounds (2.95 Kg)

Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. The manufacturer and seller make no representation or warranty, including merchantability or any other kind, expressed or implied. The foregoing may not be altered except by written agreement by officers of the manufacturer.

Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in conjunction therewith. The user should thoroughly review the material safety data sheet for this product and follow recommendations for mixing, application, disposal, and the use of any applicable personal protective equipment (PPE). The manufacturer, distributor, and seller of this product warrant that the chemical contained herein conforms to its standard specifications.



**Soil Break** is a synergistic concentration of enzymes, solvents, surfactants and builders that work together to tackle the most stubborn build-up of caked on oil, grease, protein and sticky soils in the most challenging environments.

**Soil Break** is an ultra-concentrated powder that is ideal for the pre-spraying of restaurant carpets, automotive repair centers, and other carpets that are subjected to massive amounts of oil and grease based soiling. Unlike some enzyme pre-sprays that are sensitive to alkalinity and extremely hot water, **Soil Break** contains a combination of enzymes that can be used in conjunction with your truckmount and/or high performance portable extraction equipment. This unique combination of enzymes works to accomplish the task in less time than with conventional enzyme pre-sprays. **Soil Break** breaks down surface tension fast, allowing detergents and rinse agents to clean deep down.

It has an In-use pH of 11.3-11.9, depending on dilution with a pleasing lemon fragrance. One pound of **Soil Break** can clean up to 8,000 square feet of carpet.

Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **Soil Break** with injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. Mix **Soil Break** at a rate of 2 oz. per gallon of hot tap water in a pump-up sprayer. In a standard injection type sprayer, mix 10 oz. into 5 qts. of hot tap water.
4. Pre-spray **Soil Break** on the traffic areas and let dwell for 5-10 minutes.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments use the **Evolution** cleaning wand.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

Contents: Sodium triphosphate (7758-29-4), sodium carbonate (9497-19-8), sodium metasilicate (6834-92-0), proprietary surfactants, glycol ether DPM (34590-94-8), EDTA Na4 (64-02-8), enzyme (9014-01-1), fragrance.

Read the MSDS scan here



Instrucciones:

1. Siempre antes de probar todas las soluciones de limpieza en un área oculta la estabilidad del color antes de la aplicación.
2. Para una mayor eficiencia, se aplican rotura del suelo con un pulverizador de inyección para tomar ventaja de presión de la solución y el calor creado por su alto rendimiento portátil extractor o Truckmount. También puede usar una "bomba-up" pulverizador o rociador accionado eléctrica o batería. Aplicar incluso superposición de patrones.
3. Mezclar Quiebre de suelo a una tasa de 2 oz por galón de agua caliente en un pulverizador de bomba. En un pulverizador de inyección de tipo estándar, mezclar 10 oz en 5 cuartos de galón. de agua caliente del grifo.
4. Pre-spray rotura del suelo en las áreas de tráfico para que habite durante 5-10 minutos.
5. Extraer con un detergente compatible extracción alcalina o ácido / neutralización de enjuague. Para una limpieza más rápida, reduce la fatiga y la eliminación de la suciedad más eficaz, se extrae con el RX-20 Herramienta de extracción de Rotary. En muebles ambientes densos utilizar la varita de limpieza Evolution.
6. Para un secado más rápido, especialmente en ambientes húmedos, considerar el uso de un motor axial, el aire centrífugo o de corriente descendente después de la limpieza.

Precautions and First Aid:

Keep out of reach of children. Contact may cause skin and eye irritation. Wear gloves and safety glasses when handling to avoid any contact with eyes and contact with skin in concentrate form. Use only in well ventilated areas. In case of eye contact, immediately flush with plenty of water. If irritation persists, seek medical attention. In case of skin irritation, flush with plenty of water. If ingested, drink large quantities of water and seek medical attention. Remove to fresh air in case of inhalation. See Material Safety Data Sheet (MSDS): [www.hydrmaster.com/msds](http://www.hydrmaster.com/msds) for additional safety and regulatory information.

Precauciones y Primeros Auxilios:

Mantener fuera del alcance de los niños. El contacto puede causar irritación cutánea y ocular. Use guantes y gafas de seguridad cuando manipule para evitar cualquier contacto con los ojos y el contacto con la piel en forma de concentrado. Usar sólo en áreas bien ventiladas. En caso de contacto con los ojos, lávelos inmediatamente con abundante agua. Si la irritación persiste, busque atención médica. En caso de irritación de la piel, lavar con abundante agua. Si se ingiere, beba grandes cantidades de agua y buscar atención médica. Trasladar al aire fresco en caso de inhalación. Ver ficha de seguridad (MSDS): [www.hydrmaster.com/msds](http://www.hydrmaster.com/msds) para mayor seguridad y



HydraMaster

[www.hydrmaster.com](http://www.hydrmaster.com)

425.775.7272

Part # 950-120-S Art 950-120-S R3



8 10149 01012 5