

GENERAL PUMP *A member of the Interpump Group*

Series 100 Oil

Industrial Pump Oil



- General Industrial Oil is a premium multi-purpose lubrication formulated to protect against rust and oxidation. It offers long service life and prevents sludge and varnish formation, even at high temperatures.
- General Industrial Oil possesses a high natural viscosity index. This means more constant operating characteristics over wide temperature range.
- Recommended for use in General Pump crankcases on systems requiring **less than 25 BHP**. Initial oil change after break-in period between 50 and 100 hours. Then every three months of 300 hours of operation thereafter. Check oil level in crankcase daily or before each use.
- Regular lubrication is the easiest, most efficient and least expensive element in preventive maintenance.
- **For use in GP pumps requiring up to 25 BHP. Higher BHP pumps use Series 220 oil.**

100214	6 Pack of 16 oz. Bottles
100216	12 Pack of 16 oz. Bottles

FEATURES

- Special anti-scuff and anti-wear agents extend the lives of gear, vane, radial piston and plunger pumps.
- Resists foaming and aeration.
- Highly resistant to oxidation that would result in sludge formation.
- Resists formation of harmful oil water emulsions.
- Compatible with typically used seals and gaskets.
- High viscosity index (IV) means more constant operating characteristics over wide temperature ranges.
- Low pour point assures fluid flow during cold weather operation.
- Outstanding thermal and hydrolytic stability assures long oil life.
- Exceeds wear prevention requirements of all major hydraulic pump manufactures.



General Pump
is a member of
the Interpump Group



GENERAL PUMP 1174 Northland Drive • Mendota Heights, MN 55120
Phone: (651)686-2199 • Fax: (800)535-1745 • e-mail: sales@gpcompanies.com • www.generalpump.com

Ref 300039 Rev. C
11-18

