



FastBreak HD™

High Definition Cleaning Carpet Prespray & Traffic Lane Cleaner

with
TRITANOL
1+1=3
Exclusively from
CleanMaster



FastBreak HD is a VOC compliant formula that contains the industry exclusive component Tritanol™ - an integrated blend of specialized polymers, organic sequestrants, and surfactants. With the unprecedented cleaning power and performance of Tritanol™, you will experience deep restorative cleaning in high definition. It just works better!

If for any reason you are not thrilled with the performance of FastBreak HD return it to your distributor and we'll get you a product that does.

Net Contents:
One U.S. Gallon (3.78 liters)

Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in conjunction therewith. The user should thoroughly review the material safety data sheet for this product and follow recommendations for mixing, application, disposal, and the use of any applicable personal protective equipment (PPE). The manufacturer, distributor, and seller of this product warrant that the chemical contained herein conforms to its standard specifications.

Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed.

The manufacturer and seller make no representation or warranty, including merchantability or any other kind, expressed or implied. The foregoing may not be altered except by written agreement by officers of the manufacturer.

FastBreak HD is the most ultra-concentrated (32:64-1) liquid preconditioning agent you can buy. Better than that, **FastBreak HD** is a VOC compliant formula that contains the industry exclusive component Tritanol™ - an integrated blend of specialized polymers, organic sequestrants, and surfactants. With the unprecedented cleaning power and performance of Tritanol™, you will experience deep restorative cleaning in high definition. It just works better! **FastBreak HD** is packed with soil busting, grease cutting and dissolving ingredients with an unbeatable cleaning power that out-cleans competitive products – at a safe pH of 9.5. It has special thickening agents which allow it to contain 35% more active ingredients than other pre-sprays. At the standard dilution rate of 1:32, **FastBreak HD** melts greasy soils like nothing else. On lightly soiled carpets, you can even dilute as much as 1:64 and it's still very effective. **FastBreak HD** is so effective that it will produce outstanding results on even heavily soiled commercial or residential carpets, and yet it is so safe it can be used on all synthetic fibers, even commercial wool carpets when used as directed. The alkaline builders soften water, neutralize acid soiling, dissolve and deflocculate ground in soil and sequester mineral deposits. They also help dissolve oil based soiling and prevent that soiling from re-attaching to the fiber. Finally, stabilizing additives hold the ultra-concentrated solids level of the formulation in suspension. Because **FastBreak HD** has a ready to use pH of 9.5, it can be used on stain resist residential carpets and is compliant with the warranty provisions.



Lot:



Read the MSDS,
scan here

Directions:

- Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
- For increased efficiency, apply **FastBreak HD** with an injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
- For medium to heavy soiling, mix one part solution with 32 parts water (four ounces to a gallon/.12 liters to 3.785 liters). For lighter soiling mix one part solution with 64 parts water (2 ounces to a gallon/.06 liters to 3.785 liters) For standard injection sprayer, mix one quart solution with four quarts of water into five quart container.
- For carpets with high levels of caked-on grease and oil contamination, consider boosting by adding two ounces of **GreaseBreaker** with each mixed gallon of **FastBreak HD**
- Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments use the **Evolution** cleaning wand.
- For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

Contents: Diethylene glycol butyl ether (112-34-5), Sodium Alkylnaphthalenesulfonate blend (trade secret), Tetrapotassium pyrophosphate (7320-34-5), proprietary polymers (trade secret), water (7732-18-5)

instrucciones:

- Antes de utilizar pruebe todas las soluciones limpiadoras en áreas ocultas para verificar que no afecte el color de la alfombra.
- Para incrementar la eficiencia, aplique Fast Break HD utilizando un spray de inyección para tomar ventaja de la presión de la solución y del calor creado por su extractor portátil de alto desempeño o de uno montado en una camioneta. También puedes utilizar un spray de bomba, o uno eléctrico o de baterías. Aplique uniformemente sobre la superficie.
- Para superficies medianamente o muy sucias, mezcle una parte de la solución con 32 partes de agua (4 onzas por 1 galón, 0.12 litros a 3.785 litros). Para superficies poco sucias mezcle una parte de la solución con 64 partes de agua (2 onzas por 1 galón, 0.06 litros por 3.785 litros). Para spray por inyección estándar, mezcle 1/4 de la solución con 4/4 de agua en un contenedor de 5/4.
- Para alfombras con altos niveles de contaminación por grasa y aceite, considere mejorar la mezcla agregando 2 onzas de Greasebreaker con cada galón mezclado de Fast Break HD.
- Extraiga con algún detergente alcalino compatible o enjuague neutralizador de ácidos. Para una limpieza más rápida, menos esfuerzo y mejores resultados, extraiga con el RX-20 Rotary Extractor Tool. En ambientes con muchos muebles utilice el Evolution cleaning wand.
- Para un secado más rápido, especialmente en ambientes húmedos, considere el uso de un ventilador axial, centrifugo o de corriente descendente después de limpiar.

Precautions and First Aid:

Keep out of reach of children. Contact may cause skin and eye irritation. Wear gloves and safety glasses when handling to avoid any contact with eyes and contact with skin in concentrate form. Use only in well ventilated areas. In case of eye contact, immediately flush with plenty of water. If irritation persists, seek medical attention. In case of skin irritation, flush with plenty of water. If ingested, drink large quantities of water and seek medical attention. Remove to fresh air in case of inhalation. See Material Safety Data Sheet (MSDS): www.hydramaster.com/msds for additional safety and regulatory information.



Precauciones y Primeros Auxilios:

Mantener fuera del alcance de los niños. El contacto puede causar irritación cutánea y ocular. Use guantes y gafas de seguridad al manejar para evitar cualquier contacto con los ojos y el contacto con la piel en forma de concentrado. Use sólo en áreas bien ventiladas. En caso de contacto con los ojos, lávselos inmediatamente con abundante agua. Si la irritación persiste, busque atención médica. En caso de irritación de la piel, lavar con abundante agua. Si se ingiere, beber grandes cantidades de agua y busque atención médica. Sacar al aire libre en caso de inhalación. Ver Hoja de Seguridad (MSDS): www.hydramaster.com/msds para mayor seguridad y normativas.

HydraMaster/US Products
www.hydramaster.com
425.775.7272
Part # 950-132-S Art 950-132-S-R5



8 10149 01084 2