

SAFETY DATA SHEET

Revision Date 01-May-2018

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name BIOESQUE MOLD RESISTANT COATING: CLEAR

Other means of identification

Product Code BMRCC5G

Emergency telephone number

Company Phone Number 800-921-4634 **24 Hour Emergency Phone Number** 800-424-9300

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Label elements

Emergency Overview

Appearance White Physical state liquid Odor Bland

Hazards not otherwise classified (HNOC)

Other Information

- May be harmful if swallowed
- · May be harmful in contact with skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Vinyl Acetate	108-05-4	<60	*
3-lodo-2propynyl carbamate	55406-53-6	<1	*
Methyl 2-benzimidaole	10605-21-7	<1	*
Thymol	89-83-8	<1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin Contact Rinse with clear water.

Inhalation Remove to fresh air. If not breathing, clear airway and start artificial respiration. If victim is

having trouble breathing, give supplemental oxygen, if available. Get medical attention.

Ingestion Immediately drink large quantities of water. Get medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2). Dry chemical. Foam.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dispose in accordance with federal and state regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container closed when not in use. Do not freeze. Keep out of reach of children. Follow

label instructions.

Incompatible materials Strong acids. OXIDIZERS.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies.

		tripe can a minute a commence and a construction an				
Ī	Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH		
	Vinyl Acetate	STEL: 15 ppm	(vacated) TWA: 10 ppm	Ceiling: 4 ppm 15 min		
	108-05-4	TWA: 10 ppm	(vacated) TWA: 30 mg/m ³	Ceiling: 15 mg/m ³ 15 min		
			(vacated) STEL: 20 ppm			
			(vacated) STEL: 60 mg/m ³			

Appropriate engineering controls

Engineering Controls Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear Neoprene or protective rubber gloves. Drenching safety shower and eye wash

station.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance Thick White Liquid Odor Rland

Odor threshold Color White No information available

Property **Values** Remarks • Method

Hq 8.5

BIOESQUE MOLD RESISTANT COATING (CLEAR)

Revision Date 01-May-2018

Melting point/freezing point No information available

Boiling point / boiling range 100 >212°F

Flash point No information available

Evaporation rate <

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:No information availableLower flammability limit:No information availableVapor pressureNo information available

Vapor density >1 Specific Gravity 1.03

Water solubility Miscible in water

Solubility in other solvents No information available **Partition coefficient** No information available Autoignition temperature No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available Oxidizing properties No information available

Other Information

Softening pointNo information availableMolecular weightNo information availableVOC Content (%)No information available

Density 8.51

Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Strong acids. OXIDIZERS.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO2). heat.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation Irritation and difficulty in breathing.

Eye contact Severely irritating to eyes.

Skin Contact No data available.

Ingestion Gastric pain and vomiting.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Vinyl Acetate 108-05-4	= 2900 mg/kg (Rat)	= 2335 mg/kg (Rabbit)	= 11400 mg/m^3 (Rat) 4 h = 11.4 mg/L (Rat) 4 h
3-lodo-2propynyl carbamate 55406-53-6	= 1100 mg/kg (Rat)	-	-
Methyl 2-benzimidaole 10605-21-7	= 6400 mg/kg (Rat)	= 2 g/kg (Rat)= 8500 mg/kg (Rabbit)	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

 Chemical Name
 ACGIH
 IARC
 NTP
 OSHA

 Vinyl Acetate
 A3
 Group 2B
 X

 108-05-4
 X
 X
 X
 X

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Vinyl Acetate	-	14: 96 h Pimephales promelas mg/L	52: 24 h Daphnia magna mg/L
108-05-4		LC50 static 15.04 - 21.54: 96 h	EC50
		Lepomis macrochirus mg/L LC50	
		static 26.1 - 36.63: 96 h Poecilia	
		reticulata mg/L LC50 static	
3-lodo-2propynyl carbamate	-	0.14 - 0.32: 96 h Lepomis	-
55406-53-6		macrochirus mg/L LC50 flow-	
		through 0.049 - 0.079: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		flow-through 0.05 - 0.089: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		0.18 - 0.23: 96 h Pimephales	
		promelas mg/L LC50 flow-through	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient

BIOESQUE MOLD RESISTANT COATING (CLEAR)

Revision Date 01-May-2018

Vinyl Acetate	0.73
108-05-4	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl 2-benzimidaole	U372	Included in waste streams:	-	U372
10605-21-7		K156, K158		

Chemical Name	California Hazardous Waste Status
Vinyl Acetate	Toxic
108-05-4	Ignitable

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Does not comply **IECSC** Complies Complies **KECL PICCS** Complies **AICS** Complies

<u>Legend:</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Vinyl Acetate - 108-05-4	0.1
3-lodo-2propynyl carbamate - 55406-53-6	1.0

SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Vinyl Acetate 108-05-4	5000 lb	-	-	Х

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Vinyl Acetate	5000 lb	5000 lb	RQ 5000 lb final RQ
108-05-4			RQ 2270 kg final RQ
Methyl 2-benzimidaole	10 lb	-	RQ 10 lb final RQ
10605-21-7			RQ 4.54 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Vinyl Acetate 108-05-4	X	X	X
3-lodo-2propynyl carbamate 55406-53-6	Х	-	-
Methyl 2-benzimidaole 10605-21-7	X	-	-

U.S. EPA Label Information

EPA Pesticide Registration Number Not Applicable

16. OTHER INFORMATION

NFPA Health hazards 0 Flammability 0 Instability 0 Physical and Chemical Properties -

HMIS Health hazards 1 Flammability 0 Physical hazards 0 Personal protection X

 Issue Date
 28-Apr-2018

 Revision Date
 01-May-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet
