

## 9565CV

### 5" SJS™ High-Power Angle Grinder

**POWER** : 13 AMP motor delivers 2,800 - 10,500 RPM

**PERFORMANCE** : SJS™ technology is a mechanical clutch system that helps prevent motor and gear damage

**VERSATILITY** : Variable speed control dial enables user to match the speed to the application

**DURABILITY** : Soft start suppresses start-up reaction for smooth start-ups and longer gear life

**INCLUDES** : Grinding wheel, wheel guard, side handle, inner flange, lock-nut and wrench



#### ABOUT MODEL

Makita's 5" SJS™ Angle Grinder combines 13 AMP variable speed power with comfort and motor-protection features for longer-lasting stone grinding and polishing performance. The 9565CV is engineered with Makita's innovative SJS™ mechanical clutch system to protect the gears for longer tool life.

13 AMP Power with SJS™ to Protect Gears

#### FEATURES

- Powerful 13.0 AMP motor delivers more output and variable (2,800 - 10,500) RPM
- SJS™ technology is a mechanical clutch system that helps prevent motor and gear damage by allowing the drive shaft to slip if the wheel is forced to stop
- Variable speed control dial enables user to match the speed to the application
- Constant speed control automatically applies additional power to the motor to maintain speed under load

- Soft start suppresses start-up reaction for smooth start-ups and longer gear life
- Electronic current limiter helps protect the motor from overload
- Labyrinth construction seals and protects the motor and bearings from dust and debris for longer tool life
- Slide switch with lock-on setting for continuous use
- "Tool-less" wheel guard for easy adjustment
- Zig-zag varnish protects the armature coil from dust and debris for longer tool life



## INCLUDES

- (1) 5" x 1/4" x 7/8" INOX Grinding Wheel, 36 Grit (A-95962)
- (1) 5" Tool-less Wheel Guard (135108-2)
- (1) Lock Nut (193465-4)
- (1) Lock Nut Wrench (782412-6)
- (1) Inner Flange (224378-9)
- (1) Side Handle (153489-2)

## SPECS

Wheel Diameter :	5"
AMPS :	13
No Load Speed (variable speed) :	2,800 - 10,500 RPM
Spindle Type :	5/8" - 11 UNC
Lock-On Switch :	Yes
Lock-Off Switch :	No
Switch Type :	Body grip/slide
Overall Length :	11-3/4"
Net Weight :	4 lbs.
Variable speed control dial :	Yes
Power Type :	Corded
Bind-Up Control :	Yes
Shipping Weight :	7.4 lbs.
UPC Code :	088381-033909

## RESOURCES & MEDIA

- [Makita 9565CV Instruction Manual](#)
- [9565CV Parts Breakdown](#)

## PRODUCTS RELATED TO 9565CV

Page 1 of 2



**122641-3**  
**5" Cut-off Wheel Guard**



**195236-5**  
**4-1/2"-5" Dust Extraction Surface Grinding Shroud**



**196846-1**  
**5" Dust Extractor**

