



## Ultrapac® Extreme

Ultra-powerful prespray for all cleaning challenges

FOR PROFESSIONAL USE ONLY

### Fast solubility • Superior cleaning

**BACKGROUND** Ultrapac Extreme is a general purpose carpet pre-spray for hot-water rinse extraction. It is recommended for use on water cleanable, synthetic carpeting. **Ultrapac Extreme** is compatible with both portable or truck mount extraction systems. The product includes water conditioning agents, surfactants, solvents and alkaline builders.

#### Key Features and Benefits:

- A complex buffering system keeps the pH stable to maximize cleaning potential in all conditions.
- Though a powdered product, it is fast-dissolving even in cold water.
- Ultrapac Extreme is stable up to 212°F / 100°C.
- The RTU will not separate and can be stored for several weeks
- Ultrapac Extreme is a very well balanced product. Because of this, the use of additives is neither necessary nor recommended.

**Ultrapac Extreme** is moderately alkaline with a ready-to-use pH of 11.9 to 12.3. The higher pH enhances cleaning ability but also precludes use on natural fibers or stain resist carpeting.

#### ITEMS NEEDED

*Note: be sure all equipment operates properly before arriving at the customer's location*

- Cleaning products: Ultrapac Extreme and the Prochem extraction rinse of your choice
- Optional: Powder Defoamer to control foam in the event that the carpet has high foaming residues from prior cleaning
- Personal Protective Equipment (PPE) as specified in the Safety Data Sheet (SDS)
- Supplies: booties, carpet groomer, adequate supply of clean cloths and a plastic bag for the storage of soiled cloths, measuring cup, wet floor signs, corner guards, traffic lane protectors and furniture leg protectors as needed, empty 5 gallon pail to prepare stock solution
- Equipment: air movers (the Dri-Eaz Studebaker AirPath is particularly useful in this application), vacuum cleaner (preferably a two motor upright), electric or pressure or pump up dispensers as desired for the job, either truck mount or portable extraction equipment as desired for the job.

**PRETESTING:** Check compatibility of product with the carpet prior to use.

#### INSPECTION

Inspect the customer's carpet before doing any work. Note any of the following on your inspection report and discuss with the customer:

- Air flow and drying problems within the building
- Objects that might be damaged if in contact with wet flooring such as floor length window treatments, furniture legs or skirts. Be sure to protect these items.
- Access to the work area: be sure you have room to move equipment in and out without causing damage to walls and objects in the room.
- Check the area for fragile objects. Be sure these items are removed to a safe location per customer instructions.
- Inspect and make a note of carpet for any tears, bunching, burns or other damage, excessive wear, heavy staining or unusual odors. Review any issues with the customer before proceeding.

#### PREPARATION OF SOLUTIONS

- When preparing RTU solutions, be sure to use the scoop provided with the product.
- If using an Inline injection sprayer (1:8 tip): Mix 8 scoops with enough water to make 5 quarts (4.7 L) of solution. Be sure the powder is fully dissolved.
- For use with Electric or Pump-up Sprayers: Mix 1 scoop to a gallon (3.8 L) of water.

#### Directions for use:

1. Preinspect / pretest / pretreat spots as needed.
2. Vacuum the carpet thoroughly.
3. Apply RTU solution at rate of 0.5 gallons per 100 square feet of carpet. (2 L per 10 M<sup>2</sup>) and brush or rake the carpet fibers.
4. Allow 15 minutes dwell time, but do not allow the carpet to dry.
5. Rinse extract using the rinse extraction product of choice. Follow label instructions for this product.
6. Use ventilation as needed to assure that the carpet will dry quickly.

**Sales/Tech support: 800-932-3030 • Technical support: 800-332-6037 • Emergency: 800-535-5053**

## CLEANUP

- Be sure to check for any overspray. Remove these spills promptly.
- Dispose of waste water properly. Do not dispose anywhere but to a sanitary water treatment system.
- Rinse equipment to remove product residues; these residues can interfere with valves or spray jets.

## SAFETY CONSIDERATIONS

- Avoid inhaling dust from the product when handling or preparing ready-to-use solution. If necessary, wear respiratory protection.
- Keep children and pets away from your work area, from cleaning products and from your equipment.
- If using a truck mount style extractor, remember that water supply lines and fittings will get very hot. This heat can damage lawns and some types of carpeting. The heat can also burn the skin.
- Read the Safety Data Sheets (SDSs) for all products before using them. You can obtain SDSs from your distributor or at [LegendBrandsCleaning.com](http://LegendBrandsCleaning.com).
- Use the personal protective equipment specified in the SDS.

<b>Ultracac Extreme TECHNICAL DATA</b>	
Sold as	8.695-714.0: Four 6.5 lb. / 2.9 kg jars 8.695-715.0: One 40 lb. / 18.1 kg pail 8.695-716.0: One 320 lb. / 145.0 kg drum Note: Ultracac Extreme is not currently available for sale in Canada
Color	Red
Odor	Mint
Appearance	Free flowing granules
pH of ready-to-use:	11.3 to 12.3
% phosphate as P	10%
Volatile Organic Content (VOC)	Trace