



The 5000 is a compact, ride-on floor scraper designed with a low-profile frame that increases ease of transport and maneuverability on the job.

### 5000 Specifications

Power Supply	Battery 48V	
Width*	24.5"	62 cm
Height*	48"	121.9 cm
Length*	63"	160 cm
Weight*	2,103 lb	953.9 kg
Removable Weight	455 lb	206.4 kg
Weight (Machine Only)	1,648 lb	747.5 kg
Speed	up to 160 ft/min	up to 48.8 m/min
Voltage & Frequency	115V/60Hz	230V/50Hz

### SAFETY

- A.** E-stop knob for on-the-job safety
- B.** Auto-stop feature kills machine when operator is not in seat

### COMFORT

- C.** Adjustable arm rests, seat and foot pegs for a balanced, comfortable ride

### PERFORMANCE

- D.** Front debris deflector protects the machine from loose material
- E.** Dual-lift hydraulic slide plate adjusts blade pitch and angle for continuous contact with the floor

- F.** Six AGM (Absorbed Glass Mat) 200-amp batteries

- G.** Quick-change swivel head blade holder

- H.** Precise hydraulic steering for maneuvering in tight spaces, zero turn radius, and continuous torque for higher removal rates and greater productivity

- I.** Compact design fits through door frames and elevator doors; removing the weights allows the 5000 to meet the maximum standard elevator weight restrictions

- J.** LED light for increased visibility on the jobsite

- K.** IEC 320 - universal plug allows replacement charger cords to be supplied from any country

### INCLUDED WITH THE 5000

- 5110-100: Transport Wheels
- 402929: 3/4 x 1-1/8 Wrench

- Kit 5176 includes:
  - 6277-BU: 45 degree, 3" x 12" self-scoring, bevel up
  - 6284: 3" x 12" heavy-duty blade
  - 7050-12: 12" cutting head

- One-year manufacturer's warranty on parts and labor