

460C7W





UPC Code: 07847783875

Country of Origin: Sweden - *Eligible for ARRA funded projects > \$7,443,000

Configuration:





Pin and Sleeve Devices - IEC 60309

Item Description

60 Amp, 480 Volt 3-Phase, 3P, 4W, North American Pin & Sleeve Connector, Industrial Grade, IP67, Watertight - RED

Technical Information

Electrical Specifications Amperage: 60 Amp Voltage: 480 Volt 3-Phase

Pole: 3 Wire: 4

Dielectric Voltage: 3000V for 1 min. Insulation Resistance: 500V for 1 min; >= 5M

Endurance: Up to 1000 connects and disconnects, under load, at full rated current and voltage

Current Interrupting: Certified for current interrupting at full rated current

Temperature Rise: Max 30°C temp rise at full-rated current after 50 cycles of OL at 150% rated current

Environmental Specifications

Flammability: Rated V-0 per UL94

Corrosion Resistance: Ferrous parts immersed in 20°C, 10 percent ammonium chloride solution for 10 min

Moisture Resistance: Per UL 1682. immersed for 24 hours in 5cm of 25°C

water

IP Rating: IP67, Watertight

Material Specifications

Body Material: Valox 357

Internal Cord Clamp Assembly:

Thermoplastic

External Cord Clamp Assembly: Valox

Gland Cap: Valox 357

Grommet/Gasket: Chloroprene Cover with Arm: Valox 357 Arm Spring: Performance Grade

Stainless Steel

Cover Eyelet: Nickel-Plated Brass Contact Carrier: Reinforced Nylon Phase and Ground Sleeves: Brass Sleeve Spring: Stainless Steel Terminal Screws: Steel

Internal Screws: Zinc-plated steel External Screws: Acid-Proof S/S

Mechanical Specifications

Cable Secureness: Force: 150lb, Torque: 1.0 ft-lb, Max Disp: <= 3/32" Impact Resistance: Drop from 30" 8 times after conditioning to -25°C for 6 hrs Crush Test: 250lbs for 1 min after -25°C

for 6 hrs

Minimum Withdrawal Force: 15lbs

Cord Range: .670 - 1.625

Product Features

IEC Rating: IEC 309-1 & 309-2

Color: Red


Standards and Certifications

UL Listed: 1682 and 1686 CSA Certified: C22.2 No 182.1 IEC Rating: 60309-1 and 60309-2

CE Marking: Per low voltage directives 73/23/EEC, 93/68/EEC

Warranty: 2-Year Limited

Dimensional Diagram



UNIT 286

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.201 North Service Road, Melville, NY 11747
Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2012-2014 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

*Buy American Compliant Logo -- The American Recovery And Reinvestment Act of 2009 ("ARRA") provides federal grants and loans for projects throughout the country. Section 1605 of the Act, named the "Buy American" provision, requires that certain materials and manufactured products used in projects funded by the Act be manufactured in the United States. The appearance of the Recovery Act Logo in relation to a Leviton product is only intended to reflect that such product may be used in an ARRA funded project. It does not mean that such product or Leviton is sponsored or endorsed by, or that Leviton receives funds from, the federal government or the Recovery Accountability and Transparency Board. Nothing in Leviton's use of the logo is intended to suggest anything regarding the requirements for funding under ARRA.

