

Chemsafe® Brands

Product Specifications

Item A69162 (5 gal./pail)
Item A69163 (55 gal./drum)



Product Description:

Chemsafe 200C Extra Strength Mastic/Adhesive Remover is a specially formulated product developed by Chemsafe Brands for use in the quick and efficient removal of asphaltic floor tile mastic. **Chemsafe 200C** is a CARB / OTC Compliant version of our **Chemsafe 200**. This fast-acting emulsifiable solvent quickly dissolves floor tile mastic and is equally efficient in removing spray adhesive and natural pastes and glues on tough asbestos abatement jobs. This high penetrant content softens the mastic (or adhesive) within minutes of complete saturation, and in many instances, can be completely liquefied using a squeegee or push broom. In addition, the special emulsifiers found in **Chemsafe 200C** assist in its high rinseability.

The compositions of the special blend of organic hydrocarbons found in **Chemsafe 200C** is ideally suited for use in areas where a lower concentration low odor mastic remover will not work as effectively, and should not be used in occupied areas or areas where strong odors would be of concern.

- **Very Fast-Acting**
- **≥141F Flash Point**
- **Powerful**
- **Emulsifiable**

Direction for Use:

Saturate mastic to be removed manually or with garden sprayer. Allow time for remover to penetrate and soften mastic. Dislodge with stiff broom and/or squeegee, repeat if necessary. Thoroughly rinse, wash, and/or clean treated surface upon completion of job. Surface must be completely rinsed clean and allowed to dry before any replacement materials can be installed. Dispose of in accordance with federal, state, and local regulations.

Product Data:

General ID	Hydrocarbon Mixture	Vapor Pressure (mm hg)	CARB / OTC Compliant
Odor	Mild to Mid-Range Solvent	Clean Up	Water & Detergent
Color	Clear Liquid	Reactivity	Stable
Flash Point	≥141°F	Application	Manual or Airless
Coverage	75-150 sq.ft./gal.	Shelf Life	1 Year
Vapor Density (air = 1)	> 1	Shipping Class	55
Solubility in Water	Emulsifies in Water	Shipping Weight:	5 gal. = 37 lbs. 55 gal. = 415 lbs.
Specific Gravity (water = 1)	.8077	DOT Shipping Name:	Combustible Liquid NOS
Percent Volatile	93 - 99	DOT Hazard Class	3, PGIII, NA1993
Evaporation Rate (butyl acetate = 1)	< 1	<i>If shipped under 119 gallons per container, product has been certified by DOT as being NON-REGULATED.</i>	
Boiling Range	> 300°F		

DISTRIBUTED EXCLUSIVELY BY ARAMSCO, INC. :

PHILADELPHIA (800) 767-6933	CHICAGO (800) 767 9981	HOUSTON (800) 767-8392	DALLAS (800) 767-5744	PHOENIX (800) 767-9372	NEW ORLEANS (866) 767-9180	CORPORATE-NEW JERSEY (800)767-6933	
BOSTON (800) 767-1767	HARTFORD (800) 767-7731	NEW YORK CITY (888) 767-4359	SAN JUAN (787) 880-0335	LOS ANGELES (800) 767-4620	TAMPA (800) 767-1225	DURHAM (888) 941-6368	ROCHESTER-NY (800) 767-4101