

Issue Date: 23-Jun-2011

Revision Date: 07-Jun-2022

Version 2

1. IDENTIFICATION

Product identifier

Product Name Peel Away ST-1

Other means of identification

SDS # DCI-026

UN/ID No UN1823

Recommended use of the chemical and restrictions on use

Recommended Use Paint removal from steel structures.

Details of the supplier of the safety data sheet

Supplier Address

Dumond, Inc.
253 S. Bailey Road
Downingtown, PA 19335

Emergency telephone number

Company Phone Number 1-609-655-7700

Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Blue paste

Physical state Paste

Odor No odor

Classification

Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1

Signal Word

Danger

Hazard statements

Causes severe skin burns and eye damage



Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a poison center or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a poison center or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a poison center or doctor/physician

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Calcium Hydroxide	1305-62-0	20-30
Sodium hydroxide	1310-73-2	5-10
Silica, Quartz	14808-60-7	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Seek immediate medical attention/advice.
Skin Contact	Wash thoroughly with soap and water (15-30 minutes) until no traces of the chemical remain. Remove contaminated clothing and shoes. Get medical attention if irritation occurs.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention/advice.
Ingestion	If conscious, give 1 glass of water or milk to dilute. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms	Causes painful stinging or burning of eyes and lids, watering of eyes. May cause severe chemical burns with reddening and pain. Mists and vapors cause irritation of the eyes, mucous membranes, and upper respiratory tract. May cause burns to mouth, esophagus and stomach. Swallowing large quantities may cause gastrointestinal tract irritation, nausea, vomiting, and diarrhea.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

At elevated temperatures, containers may rupture. Contents are corrosive and all personal contact must be avoided. Cool containers exposed to flames with water until well after the fire is out.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not allow into any sewer, on the ground or into any body of water. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Collect using an inert absorbent material and place in appropriate containers for disposal.

Methods for Clean-Up Keep in suitable, closed containers for disposal. Wash spill area with plenty of water. Spills and releases may have to be reported to Federal and/or local authorities. See section 15.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Protect container from physical damage. Since empty container retains residue, follow all label warnings even after container is empty. Avoid contact with skin, eyes or clothing. Do not breathe mists or aerosols. Remove contaminated clothing and shoes. Wash thoroughly after handling before eating, drinking, smoking, or using toilet facilities. Use personal protection recommended in Section 8. Use only in well-ventilated areas.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from acids and other incompatible materials. Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Incompatible Materials Acids. Flammable liquid. Organic halogen compounds. Nitromethane. Metals such as aluminum, tin, and zinc.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Hydroxide 1305-62-0	TWA: 5 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ not in effect as a result of reconsideration	TWA: 5 mg/m ³
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³
Silica, Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls

For operations where contact can occur, a safety shower and an eye wash facility should be available. Good general room ventilation (equivalent to outdoors) should be adequate under normal conditions.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Use chemical safety goggles and/or full-face shield where dusting is possible. Do not wear contact lenses.

Skin and Body Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Rubber, neoprene, or other impervious gloves are recommended to prevent skin contact.

Respiratory Protection

None needed under normal use conditions with adequate ventilation. If the occupational exposure limits are exceeded, a NIOSH approved respirator with acid gas cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Paste	Odor	No odor
Appearance	Blue paste	Odor Threshold	Not determined
Color	Blue		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	12		
Melting point / freezing point	Not available		
Boiling point / boiling range	> 100 °C / 212 °F		
Flash point	None		
Evaporation Rate	Same as water		
Flammability (Solid, Gas)	Not determined		
Flammability Limit in Air			
Upper flammability or explosive limits	Not applicable		
Lower flammability or explosive	Not applicable		

limits	
Vapor Pressure	Similar to water
Vapor Density	Same as water
Relative Density	1.33
Water Solubility	Completely soluble
Solubility in other solvents	Not determined
Partition Coefficient	Not available
Autoignition temperature	Not established
Decomposition temperature	Not determined
Kinematic viscosity	Not determined
Dynamic Viscosity	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined

Other information

VOC Content (%)	50%
VOC Content	0 lbs/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

Acids. Flammable liquid. Organic halogen compounds. Nitromethane. Metals such as aluminum, tin, and zinc.

Hazardous decomposition products

None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Eye Contact	Avoid contact with eyes.
Skin Contact	Avoid contact with skin.
Inhalation	Avoid breathing vapors or mists.
Ingestion	May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium Hydroxide 1305-62-0	= 7340 mg/kg (Rat)	> 2500 mg/kg (Rat)	-
Sodium hydroxide 1310-73-2	= 325 mg/kg (Rat)	= 1350 mg/kg (Rabbit)	-
Sorbitol	= 15900 mg/kg (Rat)	-	-

50-70-4			
Cellulose Gum 9004-32-4	= 27000 mg/kg (Rat)	-	> 5800 mg/m ³ (Rat) 4 h
Sodium xylenesulfonate 1300-72-7	= 1000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Alkyl Benzene Sulfonic Acid 85536-14-7	= 1219 mg/kg (Rat)	-	-
Soda Ash 497-19-8	= 4090 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes severe skin burns.

Serious eye damage/eye irritation Causes severe eye damage.

Carcinogenicity Silica (quartz) is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Silica, Quartz 14808-60-7	A2	Group 1	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 4,039.4795 mg/kg

Dermal LD50 6,465.50 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Sodium hydroxide 1310-73-2		45.4: 96 h Oncorhynchus mykiss mg/L LC50 static	
Alkyl Benzene Sulfonic Acid 85536-14-7	36: 72 h Desmodesmus subspicatus mg/L EC50	5.6: 96 h Cyprinus carpio mg/L LC50 flow-through	5.2: 48 h Daphnia magna mg/L EC50
Soda Ash 497-19-8		310 - 1220: 96 h Pimephales promelas mg/L LC50 static 300: 96 h Lepomis macrochirus mg/L LC50 static	265: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Calcium Hydroxide 1305-62-0	Corrosive
Sodium hydroxide 1310-73-2	Toxic Corrosive

14. TRANSPORT INFORMATION

Note Based on package size, product may be eligible for limited quantity exception.

DOT

UN/ID No UN1823
Proper Shipping Name Sodium hydroxide, solid, mixture
Hazard class 8
Packing Group II

IATA

UN number UN1823
Proper Shipping Name Sodium hydroxide, solid, mixture
Transport hazard class(es) 8
Packing Group II

IMDG

UN number UN1823
Proper Shipping Name Sodium hydroxide, solid, mixture
Transport hazard class(es) 8
Packing Group II

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Calcium Hydroxide	X	ACTIVE	X	X	X	X	X	X	X
Sodium hydroxide	X	ACTIVE	X	X	X	X	X	X	X
Sorbitol	X	ACTIVE	X	X	X	X	X	X	X
Cellulose Gum	X	ACTIVE	X		X	X	X	X	X
Silica, Quartz	X	ACTIVE	X	X	X	X	X	X	X
Sodium xylenesulfonate	X	ACTIVE	X	X	X	X	X	X	X
Alkyl Benzene Sulfonic Acid	X	ACTIVE	X	X		X	X	X	X
Soda Ash	X	ACTIVE	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sodium hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide	1000 lb			X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Silica, Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Calcium Hydroxide 1305-62-0	X	X	X
Sodium hydroxide 1310-73-2	X	X	X
Silica, Quartz 14808-60-7	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards**

3

Flammability

0

Instability

0

Special Hazards

Not determined

HMIS**Health Hazards**

Not determined

Flammability

Not determined

Physical hazards

Not determined

Personal Protection

Not determined

Issue Date:

23-Jun-2011

Revision Date:

07-Jun-2022

Revision Note:

Reformulation

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet