

Chemsafe® Brands

Product Specifications

Item 57508 - White (5 gal./pail)

Item 57509 - Clear (5 gal./pail)



Product Description:

Chemsafe 500 Lockdown is a post-removal lockdown encapsulant solution provided premixed for your convenience. **Chemsafe 500 Lockdown** is an encapsulant which provides for the lockdown of microscopic asbestos fibers to the substrate via the forming of a flexible resinous barrier. This flexible barrier also serves a dual purpose by priming the substrate and allowing for the adhesion of secondary coatings.

Chemsafe 500 Lockdown is essential for use during the mandatory sealing of microscopic asbestos fibers subsequent to asbestos removal.

Chemsafe 500 Clear is also acceptable for use as a penetrating encapsulant as provided.

- Pre-mixed
- Available in Clear or White
- Economical
- CARB / OTC Compliant

Chemsafe 500 is an unclassified lockdown encapsulant that has been tested for ambient temperature bond strength with Monokote MK6/HY and RG materials and can be applied to beams, columns, pipes, tube steel and open web steel joists only. Additional mechanical attachment may be required depending upon steel size per the Coating Materials section of the UL Fire Resistant Directory.

Direction for Use:

For best results apply **Chemsafe 500 Lockdown** with an airless sprayer. Consult your **Chemsafe Brands** field representative for proper pressure settings and tip sizes. Dispose of in accordance with federal, state, and local regulations. Clean spray equipment and tools immediately after use with warm water prior to product drying.

Product Data:

General ID	Acrylic Emulsion Polymer	Boiling Range	212°F
Odor	Negligible Odor	Vapor Pressure (mm hg)	25mm hg
Color	500C applies white - dries clear 500W applies white - dries white	Clean Up	Water & Detergent
Flash Point	N/A	Reactivity	Stable
Coverage	500 sq.ft./gal.	Application	Manual or Airless
Vapor Density (air = 1)	1	Shelf Life	2 Years
Solubility in Water	Complete	Shipping Class	55
Specific Gravity (water = 1)	.9832	Shipping Weight:	5 gal. = 45 lbs.
Percent Volatile	< 12	DOT Shipping Name:	Not Regulated
Evaporation Rate (butyl acetate = 1)	< 1	DOT Hazard Class	Non Hazardous

.....
DISTRIBUTED EXCLUSIVELY BY ARAMSCO, INC. :

PHILADELPHIA (800) 767-6933	CHICAGO (800) 767 9981	HOUSTON (800) 767-8392	DALLAS (800) 767-5744	PHOENIX (800) 767-9372	NEW ORLEANS (866) 767-9180	CORPORATE-NEW JERSEY (800)767-6933	
BOSTON (800) 767-1767	HARTFORD (800) 767-7731	NEW YORK CITY (888) 767-4359	SAN JUAN (787) 880-0335	LOS ANGELES (800) 767-4620	TAMPA (800) 767-1225	DURHAM (888) 941-6368	ROCHESTER-NY (800) 767-4101