


# DUCTMATE

## DUCT ACCESS DOORS


Rectangular – “The Sandwich”

Airtight pressure vessel design. Features galvanized steel outer door, high-density fiberglass insulation and galvanized steel inner door with flat inside cover and closed-cell neoprene gasket. Plastic hand knobs feature metal inserts and zinc coated springs. Tested to pressures of +20" and -10" WG. Includes self-adhesive template for installation.



No.	Dim. In. L x H
DI106GA	10 x 6
DI128GA	12 x 8
DI1814GA	18 x 14
DI2418GA	24 x 18

## GREASE DUCT ACCESS DOORS



Features galvanized steel outer door with permanently bonded ceramic fiber gasket, galvanized steel inner door with smooth

inside cover, and 16-ga. black iron backing plate. Zinc coated wingnuts with conical springs for opening and closing. Gasket rated to 2300°F; meets NFPA 96 standards. Includes self-adhesive template for installation.

No.	Dim. In. L x H
DMAD-1006	10 x 6
DMAD-1208	12 x 8
DMAD-1814	18 x 14

## GREASE DUCT ACCESS DOORS

### Ultimate

Sandwich design reduces installation time, eliminates need for welding and minimizes duct penetration. Grease-tight. Black iron construction. UL and CUL listed. Meets NFPA 96 standards.




No.	Dim. In. L x H	
	Opening	Door
D66ULBI	6 x 6	8 x 8
D106ULBI	10 x 6	12 x 8
D128ULBI	12 x 8	14 x 10

# MILCOR

## ACCESS DOORS

Fire-Rated – Model MIL-FR



For use in wall and ceiling applications including drywall, masonry and suspended acoustical ceilings. Features 16-ga. steel frame with 20-ga. door panel, 2" mineral fiber insulation for reduced sound transmission, continuous hinge with stainless steel pin, and factory installed masonry anchors. Self-latching. UL and CUL class B fire rated.


No.	Dim. In.	
	Opening	Door
MIL-FR-12	12-1/2 x 12-1/2	12 x 12
MIL-FR-24	24-1/2 x 24-1/2	24 x 24



**THOMAS ENTERPRISES**

## ACCESS PANELS

Fire-Rated – Model FD



Provides access to utilities in walls or ceilings of stairwells, shafts and corridors. Features 20-ga. steel door with automatic close/latch mechanism and 2" insulation; 16 ga. steel frame with masonry anchors and bolt holes. Gray enamel finish. UL and WHI listed.


No.	Door	Dim. In.	
		Wall Open.	Ceiling Open.
FD 12	12 x 12	12-3/8 x 12-3/8	13-5/8 x 13-5/8
FD 18	18 x 18	18-3/8 x 18-3/8	19-5/8 x 19-5/8
FD 24	24 x 24	24-3/8 x 24-3/8	25-5/8 x 25-5/8



# Babcock-Davis

## ACCESS DOORS

Fire-Rated – Model WBFR



For vertical wall applications. Features 16-ga. steel frame, 18-ga. steel door, 1-7/8" mineral wool insulation, concealed pivot-type hinge, automatic closer and inside release. 140° opening angle. Self-latching. Gray enamel finish. UL and Warnock Hersey listed.

No.	Dim. In.	
	Opening	Door
WBFR-1212	12-1/4 x 12-1/4	12 x 12
WBFR-1818	18-1/4 x 18-1/4	18 x 18
WBFR-2424	24-1/4 x 24-1/4	24 x 24



Flexible Duct, Sheet Metal Fittings, Access Doors and Accessories

## DUCT ACCESS DOORS

“The Inspector” – Model RDDRSM



Sheet metal construction with spin design and low leakage rate (less than .10 CFM @ 6" w.g.).

No.	Dim. In.
RDDRSM-08	8
RDDRSM-10	10
RDDRSM-12	12
RDDRSM-18	18

**Check our website for special promotions.**

[www.tombarrow.com](http://www.tombarrow.com)